

Fire safes FS-series are great choice for fire protection. Special wall and door filling provides 30 minutes fire resistance for your valuables. Great range of sizes Certified for fire resistance grade LFS 30 P according to EN 15659 Thermal stripe BASF (Germany) round door perimeter Protective layer of 45 mm thick filled fireproof concrete 1 side active chromized bolts Ø25 mm and 3 fixed girth rails on the hinges side Adjustable shelves Anchor bolts to fix safe to the floor Standard color: body - anthracite-grey, (RAL 7016) door - cream, (RAL 9001) Could be equipped with STUV(Germany) VdS Class 1 EN 1300 key lock or Griffon electronic code lock (with or without emergency key)

Specifications

Safe type

Safe type fire resistant

External dimensions, mm

Height 900 mm

Width 500 mm

Depth 455 mm

Internal dimensions, mm

Height 798 mm

Width 412 mm

Depth 308 mm

General

Internal volume, L 101

Weight, kg 123

Overall protective layer thickness, mm 43

Locking system three-sided bolt locking system (4 chromium active rotary bolts diameter 25mm), anti-cuts at hinges side

Lock type key safe emergency lock STUV (Germany), VdS Class 1, safe electronic code lock

Fire resistance LFS 30P class EN 15659

Coating type powder paint coating

Color anthracite-grey, creme-white (RAL 7016, RAL 9001)

Safe series FS

Basic set

Inner lockable box 1

Shelves 1

Auxiliaries BASF(Germany) thermal tape at door contour; anchoring to floor ready