

Burglar-resistant safe series CLE.II are ECB-S certified with total protective layer thickness 55mm Safes are grade II certified as per EN 1143-1 by ECB-s Safes meet the requirements for protection level LFS 30 P for fire resistance according to EN 15659 Burglar-resistant system of relockers Safe doors are equipped with strong three-sided bolt locking system, 5 active chromized bolts Ø25 mm and 3 fixed bolts on the hinges side Tempered high alloyed steel plates to protect locks and bolts from drilling and kicking out. The protective layer of the case and door with fortification concrete – 55 mm thickness The structure provides the possibility to fix the safe to floor by anchors BASF thermal tape (Germany) along the perimeter of the door to protect from fire Standard color: dark grey, cream Interior fabric decoration options available Could be equipped with STUV(Germany) VdS Class 1 EN 1300 key lock; M-Locks(Netherlands) VdS Class 2 EN 1300 electronic code lock; La Gard(USA)/M-Locks(Netherlands) VdS Class 2 EN 1300 mechanical combination lock or both STUV(Germany) VdS Class 1 EN 1300 key lock and La Gard(USA)/M-Locks(Netherlands) VdS Class 2 EN 1300 mechanical combination lock

Specifications

Safe type

Safe type fire and burglar resistant

External dimensions, mm

Height 1506 mm

Width 600 mm

Depth 600 mm

Internal dimensions, mm

Height 1390 mm

Width 490 mm

Depth 430 mm

Internal volume, L 293

Weight, kg 430

Rifles could be stored 4

Overall protective layer thickness, mm 55

Burglar resistance Grade II EN 1143-1

Locking system three-sided bolt locking system (5 active chromized rotary bolts diameter 25 mm, anti-cuts at hinges side)

Lock type safe key lock STUV(Germany) VDS class 1, safe electronic code lock M-LOCKS (The Netherlands) VdS class 2 with delay opening function

Fire resistance LFS 30P class EN 15659

Coating type enamel coating with hammer effect

Color dark-grey enamel with hammer effect

Safe series CLE