

Fire safes FS-series are great choice for fire protection. Special wall and door filling provides 30 minutes fire resistance for your valuables. Great range of sizes Certified for fire resistance grade LFS 30 P according to EN 15659 Thermal stripe BASF (Germany) round door perimeter Protective layer of 45 mm thick filled fireproof concrete 1 side active chromized bolts Ø25 mm and 3 fixed girth rails on the hinges side Adjustable shelves Anchor bolts to fix safe to the floor Standard color: body - anthracite-grey, (RAL 7016) door - cream, (RAL 9001) Could be equipped with STUV(Germany) VdS Class 1 EN 1300 key lock or Griffon electronic code lock (with or without emergency key)

## **Specifications**

### **Safe type**

Safe type fire resistant

### **External dimensions, mm**

Height 560 mm

Width 445 mm

Depth 445 mm

### **Internal dimensions, mm**

Height 458 mm

Width 359 mm

Depth 303 mm

### **General**

Internal volume, L 49,5

Weight, kg 75

Overall protective layer thickness, mm 43

Locking system bolt locking system (3 active chromized rotary bolts diameter 25 mm), anti-cuts at hinges side

Lock type electronic code lock

Fire resistance LFS 30P class EN 15659

Coating type powder paint coating

Color anthracite-grey, creme-white (RAL 7016, RAL 9001)

Safe series FS

### **Basic set**

Shelves 1

Auxiliaries BASF(Germany) thermal tape at door contour; anchoring to floor ready