

## Smarter Way to Print ID



• **CP55-S**  
SINGLE SIDE



• **CP55-D**  
DUAL SIDE

Heidi CP55 is a high-speed direct-to-card printer built to deliver innovative imaging and excellent printing quality at a competitive cost-per-card. It is a highly adaptable solution designed to serve many sectors within various user environments and card-issuance operations. Heidi CP55 is simply deployed, operated and maintained.

### Heidi CP55 empowers users with the following benefits:

#### User-Friendly

Easy-to-use and maintain, simply plug and print.

#### Durable yet affordable

Reliable operations, high-resolution printing offered at a reasonable price.

#### Highly Scalable

An all-in-one printing solution with upgradable options, ribbons and software.

#### Trusted Security

Contact, contactless, and MS encoding for high-standard digital security compliance with EMV. Equipped with physical lock.

#### Smart Design

Compact size with a unique design, ideal for limited workspaces.

**Heidi CP55 at a glance:**

- Innovative printing technology
- Remarkable quality with 300x300 dpi
- Smart and elegant design
- Single and Dual side printing
- Optional integrated encoders and Ethernet

## Key Features

### Capabilities

The CP55 is a high-quality printer with 300x300 dpi, edge-to-edge printing on various types of cards and thickness with a wide range of ribbons.

### Operation

All-in-one ribbon cassette and cleaning roller simplifies ribbon loading and cleaning processes. Easily operated LED indicators, buttons and instant system status LCD display.

### Performance

The built-in 64 MB memory facilitates the high-speed storing and processing of printing jobs.

### Personalization

Provides multiple options for protection against card tampering fraud attempts by adding a covert layer of security using an ultra-violet (UV) ribbon along with smart card encoding. It supports the secure global EMV standard, ensuring that cards are interoperable with the global payment infrastructure.

### Modularity

Seamlessly upgrade the basic CP55 single-side printer to a dual-side with a flipping unit, as well as magnetic-stripe, contact and contactless encoders.

## Technical Specs | CP55 Specifications Sheet

Standard Features	CP55-S (Single-Sided Printer)	CP55-D (Dual-Sided Printer)
<b>Printing speed</b>	Color (YMCKO): up to 170 cards/hour	Color (YMCKOK): up to 130 cards/hour
	Half Color (HYMCKO): 200 cards/hour	
	Black Overlay (KO): up to 360 cards/hour	
	Mono (Black, Gold, Silver): up to 720 cards/hour	
<b>Printing method</b>	Direct-to-card dye-sublimation/resin thermal transfer	
<b>Printing capability</b>	Dual-side and single-side edge-to-edge printing, ultra-violet fluorescent printing, in full-color and monochrome	



Standard Features	CP55-S (Single-Sided Printer)	CP55-D (Dual-Sided Printer)
Accepted standard card sizes/format	ISO CR-80 (3.375"L x 2.125"W/85.6 mm L x 54 mm W)	
Accepted card thickness	0.38mm (15mil) ~ 1.0mm (40mil)	
Accepted card types	Printable PVC, Printable PET, Printable PC	
Resolution	300 dpi (11.8 dots/mm)	
Print area	CR-80 (3.36"L x 2.11"W/85.3 mm L x 53.7 mm W)	
Print ribbon options	Full-color with resin black and overlay panel, YMCKO, 250 prints/roll	
	Full-color with two resin black panels and overlay panel, YMCKOK, 200 prints/roll	
	Resin black with overlay panel, KO, 600 prints/roll	
	Mono (Black, Gold, Silver): 1,200 cards/roll	
	YMCUV0 Blue: 200 prints/roll	
	Half YMC Full KO: 350 prints/roll	
Input hopper card capacity	100 cards (200 cards with cover open)	
Output hopper card capacity	40 cards (100 cards with option back side stacker)	
Card cleaning	Cleaning roller with each cartridge	
Memory	ROM: 2MB, RAM: 64MB	
Software	GET Identity	
Interface	USB 2.0, Ethernet with option	
Display	2 Lines LCD & LED indicator	
CPU	AM3352 600MHz	
Power	Free Voltage (110/240V AC), 50 ~ 60 Hz, 45W	
Operating environment	Temperature: 20 ~ 35°C, Humidity: 20 ~ 80%	
Certification	CE, CB, FCC	
Operating system support for printer driver	Windows 7/8/10, Linux, Mac	
Warranty	24-months standard depot warranty   24 months print head warranty	
Physical lock	Optional, top cover lock	
Kensington lock	Back side	
Dimensions	380mm(W) x 208mm(H) x 166mm(D)	486mm(W) x 208mm(H) x 166mm(D)
Weight	5.1 kg	6.0 kg

## Field Upgradable Options

	CP55-S	CP55-D
<b>Flipper</b>	Optional dual-side print module	Default
<b>Magnetic stripe encoder</b>	ISO7811 (Track I, II, III Read/Write) HiCo/LoCo	
<b>Contact smart card encoder</b>	ISO/IEC 7816-1,2,3,4: IC Cards with contacts, EMV Terminal Level 1 version 4.1	
<b>Contactless smart card encoder</b>	ISO14443(Type A/B), MIFARE ®, MIFARE DESFire ®, iClass ®, EMV2 2000 Level 1	
<b>Ethernet</b>	TCP/IP 10/100 BaseT	

## GET Identity

This versatile, reliable and tool-rich card personalization system is trusted by public and private institutions across the globe, precisely and comprehensively assisting in the design and issuance of millions of highly secure ID cards. Suitable for simple student IDs, as well as complex cards such as access control and loyalty programs.

